



TEMPORARY PAVEMENT

N.T.S.

NOTES

1. TEMPORARY PAVEMENT MATERIAL IS TO BE 1 1/2" INCHES THICK ASPHALT CONCRETE BINDER COURSE, TYPE 3 . ASPHALT COLD PATCH AND UNTREATED MILLING MATERIALS ARE UNACCEPTABLE FOR USE.
2. DURING WINTER SEASON (NOVEMBER 1 THRU APRIL 14), IF A HOT MIX ASPHALT MATERIAL IS NOT AVAILABLE, USE CLASS F CONCRETE. CONCRETE IS TO BE 4 INCHES THICK FOR ARTERIAL AND COLLECTOR STREETS, 3 INCHES THICK FOR RESIDENTIAL STREETS AND BROOM FINISHED.
3. TEMPORARY PAVEMENT IS TO BE PLACED WITHIN 24 HOURS AFTER BACKFILLING TRENCH OR EXCAVATION.
4. ALL MATERIALS ARE TO BE COMPACTED TO FORM A FIRM AND SMOOTH SURFACE.

JULY 2010

REVISIONS		TOWN OF BATAVIA
DATE	COMMENTS	HIGHWAY & STORM SEWER DETAILS
		TEMPORARY PAVEMENT
		DRAWING HS-24